

前面
FRONT PANEL

1

2

3

4

66

21

80

122

LED Luminar

POWER

BRIGHT CONTROL
EXT.IN (REAR)

INTERNAL

BRIGHT LEVEL ADJUST

LAMP 1

LAMP 2

HIGH

LOW

HIGH

LOW

NISSIN ELECTRONIC CO.

MODEL CRD-30W-A JAPAN

MOUNTING
4-M3

Technical drawing of the front view of a rectangular device. The drawing shows a rectangular frame with a central area containing two rows of horizontal slots. The top row has six slots, and the bottom row has six slots. Below the bottom row, there are two circular symbols, each containing a plus sign (+). The dimensions are indicated by arrows and numbers: a vertical dimension of 12 on the left, a horizontal dimension of 180 across the top, and a horizontal dimension of 204 across the bottom. The drawing is labeled 'Fig. 1' in the bottom right corner.

Diagram of the CRD-30W-A model showing terminal connections. The diagram includes labels for 'OUTPUT' (5), 'EXTERNAL SIGNAL IN' (6), 'LAMP 1', 'LAMP 2', 'LAMP ON/OFF' (PIN 1 2 3 4 5 6), 'DC24V IN 5A' with polarity (+, -), 'FG' (7), and 'MADE IN JAPAN'. The model name 'MODEL CRD-30W-A No. NISSIN ELECTRONIC CO.' is also present.

- 外形寸法 W122.H66.D204(突起部含まず)
重量 約1.2kg
外装色 マリンブルー・レサートーン
外装仕上 焼付塗装

H	△	- -			
	△	- -			
	△	- -			
	△	- -			
	△	- -			

[illegible]